



 Change Region Language: English (UK)
[Aerial Work Platforms](#) » [Mast Boom Lifts](#) » [Toucan 10E](#)

Toucan 10E Specifications

[Specifications](#)
[Comparison](#)


[Home](#)
[Products](#)
[Aerial Work Platforms](#)
[Telehandlers](#)
[Services](#)
[Used Equipment](#)
[Career Center](#)
[Safety](#)
[About JLG](#)
[My JLG](#)
[Contact Us](#)
[Distributor Locator](#)

Power Source

Batteries	24V - 240 A/hr
Battery Charger	24V - 25A
Drive Motors	Dual AC Motors
Brakes	Disc
Electrical Motor	3kW 24Vdc
Hydraulic Reservoir	9 L

Reach Specifications

Platform Height	8.10 m
Working Height*	10.10 m
Horizontal Outreach**	3.08 m
Up and Over Height	6.51 m
Mast Rotation	345°
Platform Capacity	200 kg
Platform Rotator	n/a
Jib (Size)	1.60 m
Jib (Range of Articulation)	+66°, -61° Vertical

Dimensions

Platform Size (W x L)	0.90 x 0.70 m
Overall Width	0.99 m
Tailswing	13 cm
Stowed Height	1.99 m
Stowed Length	2.82 m
Wheelbase	1.20 m
Ground Clearance	10.5 cm
Weight***	2,990 kg
Ground Bearing Pressure****	21.0 kg/cm ²

Chassis

Drive Speed	5.5 km/h
Gradeability	25%
Turning Radius - Inside	0.55 m
Turning Radius - Outside	1.99 m
Tire Size	406 x 125 mm
Tire Type	Solid Non-Marking
Electrical System	24V DC