



- [Home](#)
- [Products](#)
- [Services](#)
- [Used Equipment](#)
- [Career Center](#)
- [Safety](#)
- [About JLG](#)
- [My JLG](#)
- [Contact Us](#)
- [Distributor Locator](#)



EXTENDING YOUR REACH

[Change Region](#)

Language:
English (UK) ▾

Search

[Aerial Work Platforms](#) » [Electric Scissor Lifts](#) » [Electric Liftflux™](#) » [153-12](#)

153-12 Specifications

Dimensions

Platform Height - Elevated	15.30 m
Platform Height - Lowered	2.10 m
Platform Railing Height	1.10 m
Overall Height	3.20 m
Overall Height w/ Rails Lowered	2.50 m
Platform Dimensions	1.16 x 3.91 m
Platform Length Fully Extended	5.40 m
Overall Length	4.12 m
Overall Width	1.22 m
Wheelbase	2.90 m
Ground Clearance	11 cm
Platform Capacity	500 kg
Capacity on Extension	500 kg
Lift/Lower Time	70/50 seconds
Maximum Drive Height	7.00 m
Weight* (CE)	7,300 kg
Ground Bearing Pressure**	14kg/cm ²

Power Source

Batteries	2 x 24V , 350 A/hr Gell Traction Cell
Charger	40 Amp Automatic SCR
Electric Pump Motor	2 x 3.7 kW
Drive Motors	Hydraulic
Pump	2 x Single Section Gear Pump
Hydraulic Reservoir	55 L

Chassis

Drive Speed, Lowered	2.50 km/h
Drive Speed, Elevated	0.70 km/h
Gradeability 2WD/AWD	15%
Turning Radius - Inside	1.60 m
Turning Radius - Outside	4.10 m
Tyre Size	639 x 220 x 480
Tyre Type	Non-Marking

Brakes Spring Applied Hyd. Released Discs

[Specifications](#)
[Accessories](#)

[Print Model](#)



Copyright © 2012 JLG Industries [Site Terms of Use](#) | [Media](#) | [Merchandise](#) | [Site Map](#)

[An Oshkosh Corporation Company](#)

